

CONNECTIVITY CARD NRF91 MPCIE

Datasheet. Release 1.0

Remote monitoring of critical infrastructure with edge computing

The nRF91 Connectivity Cards from CTHINGS.CO® are extension cards based on the Nordic® Semiconductor nRF9161 SoC. They are multi-protocol chips designed to empower IoT integrators to implement DECT NR+, LTE Cat-M1/NB1/NB2 protocol stacks.

The extension card allows for full-fledged utilisation of the on-board Arm® Cortex®-M33 CPU with FPU. In addition, the ARM TrustZone® CryptoCell 310 cryptographic unit brings an extensive range of cryptography options.

The product comes with full CE class-B and RED certification and can be used to quickly and reliably add LTE or DECT NR+ protocol stack support to any existing device with a **mini-PCIe** without worrying about certification or radio performance. A full J-Trace connector is available for convenient firmware development.

CTHINGS.CO also provides various pre-flashing options, and tested support for Wirepas 5G Mesh firmware profile.

SPECIFICATIONS

Hardware Features	<ul style="list-style-type: none"> • Mini PCI-express connector pinout compliant • Single-ended U.FL antenna connector • Based on Nordic® Semiconductor nRF9161 • 64 Mbit flash memory • Ultra-low power consumption • J-Trace interface for easy debugging and FW development • Arm® Cortex®-M33 processor with FPU, 64 MHz • Communicating with host device via USB interface
Software Features	<ul style="list-style-type: none"> • Compatible with Wirepas Mesh 5G NR+ profile firmware (including sink) • Compatible with nRF Connect SDK
Electrical Specification	<ul style="list-style-type: none"> • 3.3 V nominal supply voltage (electrically mini-PCIe compliant) • 3.0 V - 3.5 V supply voltage range • ESD protected • Ultra-low power consumption
Modem features	<ul style="list-style-type: none"> • 3GPP LTE release 14 Cat-M1 compliant • 3GPP LTE release 14 Cat-NB1 and Cat-NB2 compliant • Power Saving Modes: DRX, eDRX, PSM • GPS L1 C/A supported • QZSS L1 C/A supported • DECT NR+ band: 1, 2, 9
RF transceiver for global coverage	<ul style="list-style-type: none"> • Up to 23 dBm output power • RX sensitivity: <ul style="list-style-type: none"> • -108 dBm for Cat-M1 • -114 dBm for Cat-NB1 and Cat-NB2 • Supports LTE bands from 700 MHz to 2.2 GHz through a single 50 Ω antenna pin
LTE band support in hardware:	<ul style="list-style-type: none"> • Cat-M1: B1, B2, B3, B4, B5, B8, B12, B13, B18, B19, B20, B25, B26, B28, B66, B85 • Cat-NB1/NB2: B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B65, B66, B85
Embedded Security	<ul style="list-style-type: none"> • ARM® TrustZone® Cryptocell 310 security subsystem • Secure boot ready • Secure erase

SPECIFICATIONS

Certifications

The CTHINGS.CO® nRF91 mPCIe 5G Suite Connectivity Card is CE Class-B, Radio Equipment Directive (RED), & EU RoHS directive compliant. US FCC and UK CA certification is planned. The device has been tested to meet the following electromagnetic compatibility standards:

Electromagnetic emissions:

- Conducted emission: EN 55022, EN 55014-1, EN 55011
- Radiated emission up to 6 GHz
- Harmonic current emission: EN 61000-3-2
- Voltage fluctuations and flicker: EN 61000-3-3

Immunity to electromagnetic interference (EMI):



- Electrostatic discharge (ESD) immunity: EN 61000-4-2
- Radiated electromagnetic field immunity: EN 61000-4-3
- Electrical fast transient / burst immunity: EN 61000-4-4
- Surge immunity: EN 61000-4-5
- Conducted disturbance immunity: EN 61000-4-6
- Power frequency magnetic field immunity: EN 61000-4-8
- Pulse magnetic field immunity: EN 61000-4-9
- Voltage dips & short interruptions: EN 61000-4-11

Use Cases

- IoT Gateways
- Workstations and Laptops
- Cellular backhaul systems for non-cellular Wirepas meshes
- Bluetooth interface for IoT sensors
- Gateways for Nordic® Semiconductor nRF91 based IoT systems

Wirepas 5G Mesh	Plug-and-play support for Wirepas 5G / NR+ profile mesh networks	Mini-PCIe Pinout Compliance	Small and standardised form factor compliant with common hardware
Cellular LTE Network	Cat. M1, NB-IoT (Cat. NB1/NB2)	Multiprotocol	LTE, GPS, DECT NR+, Wirepas 5G Mesh,
Certified Radio Equipment	Full CE Class-B & Radio Equipment Directive (RED) certification	Performant CPU	32-bit ARM Cortex-M33 CPU with floating-point unit

External appearance



Confidentiality



This document is based on information provided by CTHINGS.CO Sp. z o.o. (the “Company”). It is being communicated on behalf of the Company to you solely for information and for the exclusive use of the selected persons to whom it is addressed for the purpose of their considering whether to proceed with a further analysis of a potential transaction (the “Transaction”) involving the Company. This document should not be used for any other purpose. This document is strictly confidential and cannot be disclosed, revealed, reproduced or redistributed, in whole or in part, by or to any other person without the prior written consent of the Company.

All rights reserved



No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of the publisher, including brief quotations embodied in critical reviews and other non-commercial uses permitted by copyright law. The publisher makes no representations or warranties with respect to the accuracy or completeness of the contents of this document. The publisher does not make any commitment to update the information contained herein. The publisher's products are not intended, authorised, or warranted for use as components in applications intended to support or sustain life. The publisher's products are not designed for and will not be used in connection with any applications where the failure of such products would reasonably be expected to result in significant personal injury or death.

Disclaimer



The information herein is believed to be correct as of the date issued. The Company will not be responsible for damages of any nature resulting from the use or reliance upon the information contained herein. The Company makes no warranties, expressed or implied, of merchantability or fitness for a particular purpose or course of performance or usage of trade. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy, and safety. Users should obtain the latest relevant information before placing orders.

Unless The Company has explicitly designated an individual product as meeting the requirement of a particular industry standard, The Company is not responsible for any failure to meet such industry standard requirements.

Unless explicitly stated herein this document, The Company has not performed any regulatory conformity test. It is the user's responsibility to assure that necessary regulatory conditions are met and approvals have been obtained when using the product. Regardless of whether the product has passed any conformity test, this document does not constitute any regulatory approval of the user's product or application using the product.

Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right. No license, expressed or implied, to any intellectual property right is granted by The Company herein.

The Company reserves the right to at any time correct, change, amend, enhance, modify, and improve this document and/or products without notice. This document supersedes and replaces all information supplied prior to the publication hereof.